

## DESCRIPTION

**ATF SYN LV** is a new generation, low viscosity, full synthetic fluid developed for transmissions requiring a lighter viscosity fluid compared to SYN MULTITRANS. ATF SYN LV is designed to meet the current low viscosity requirements of many OEM vehicle manufacturers. The ideal transmission fluid where Ford Mercon LV and GM Dexron VI are required plus many other applications.

## SUMMARY OF BENEFITS

ATF SYN LV is a very versatile fluid and can be used in almost all Japanese and many European and American vehicles as a service fill and may also be used as a power steering fluid and in hydraulic systems particularly where high temperatures are encountered.

## SPECIFICATIONS

- AISIN WARNER AW-1
  - AISIN 8 SPEED (AA80E, TR-80SD (0C8), TR-82SD)
  - AUDI G 055 005, G 055 162
  - BMW 83 22 0 142 516, 83 22 2 152 426
  - HONDA DW-1
  - FORD MERCON LV
  - GM DEXRON -VI
  - GM 8 SPEED (GM 8L90)
  - HYUNDAI/KIA SP-IV, SPH-IV, SP-IV RR
  - HYUNDAI NWS-9638
  - JASO 1-A-LV
  - JWS 3324
  - MAZDA ATF FZ
  - NISSAN MATIC-S, MATIC-W
  - MITSUBISHI SP-IV, ATF J2, ATF J3, ATF-PA, MA1
  - SAAB 93 165 147
  - VOLVO 6 SPEED MY (2011 – 2013) PN 31256774 OR 31256675
  - TOYOTA WS (JWS 3324)
  - VW G 055 540, G 055 005, G055 162
  - ZF 6 SPEED (S671 090 255)
  - ZF 8 SPEED, ZF 9 SPEED
  - MERCEDES BENZ MB: 236.12, 236.14, 236.41
- Available in Red – Product Code 9380*  
*Available in Clear – Product Code 9385*  
**More specifications next page.**

## TECHNICAL DATA

CHARACTERISTICS	ATF SYN LV
Specific gravity at 15 C	0.845
Kinematic viscosity at 40 C, mm <sup>2</sup> /s (cSt)	29
Kinematic viscosity at 100 C, mm <sup>2</sup> /s (cSt)	5.9
Viscosity index	154

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website [www.tritechlubricants.com](http://www.tritechlubricants.com)
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

## Complete specifications:

Audi/VW G 055 005 -A, -A1, -A2, -A6 (ZF LifeguardFluid 6) (ZF No. S671 090 255)	Honda Type 3.1 : 08263-999-01HE (EU), 08200-9017 (USA) (ZF LifeguardFluid 9) (ZF No. AA01.500.001)	Nissan Matic Fluid W
Audi/VW G 055 162-A2, -A6 (ZF LifeguardFluid 6 Plus) (ZF No. S671 090 281)	Honda Ultra HEVF-Type 1	Saab 93 165 147
Audi/VW G 060 162 (ZF LifeguardFluid 8) (ZF No. S671 090 312)	Hyundai/Kia SP-IV (00232-1904/04500-00115)	Saab Power Steering Fluid 2634, 45 30 09 800, 93160548
Audi/VW G 055 540 A2	Hyundai/Kia SP-IV M (SP4-M)	Shell M-1375.4
Bentley PY112995PA	Hyundai/Kia SPH-IV	Shell L 12108
BMW ATF 2	Hyundai/Kia SPH-IV M1 (SP4-M1)	Suzuki ATF AW-1
BMW ATF 3+	Hyundai/Kia SP-IV-RR	Toyota ATF WS
BMW ATF 6	Hyundai/Kia NWS 9638	Volvo PN 31256774/31256675
BMW ATF 7	Hyundai/Kia 040000C90SG	VW G055 540 (A2)
Chrysler/Dodge/Jeep 68043742AA	ISUZU ATF WSI	VW G 055 005-A, -A2 (ZF LifeguardFluid 6)
Chrysler/Dodge/Jeep 68157995AA	Jaguar Fluid 8432	VW G 055 162-A2, -A6 (ZF LifeguardFluid 6 Plus)
Chrysler/Dodge/Jeep 68157995AB	Jaguar 02JDE26444	VW G 060 162 (ZF LifeguardFluid 8)
Chrysler/Dodge/Jeep 68218925AA and 68218925AB	JASO M315-2015 1A-LV	ZF 6 speed transmissions
Chrysler/Dodge/Jeep MOPAR SP IV, 68171866AA/68171869AA	Land Rover TYK500050	ZF 8 speed transmissions
FIAT 9.55550-AV5	Land Rover LR0022460	ZF 9 speed transmissions
Ford ATF C-ML5	Land Rover LR023288	Service-fill for 8 and 9 speed step-ATs
Ford/Lincoln/Mercury XT-6-QSP or -DSP (SP)	Maserati 231603	Ford Escape Hybrid eCVT
GM 1940767	Mazda ATF M-V	Honda e:HEV
GM Transfer Case (AutoTrak II)	Mazda ATF FZ	Mazda SKYACTIVE-HYBRID
GM/GMC/Opel/Saturn AW1	Mitsubishi Diaqueen J3	Nissan Altima Hybrid
GM/GMC/Opel/Saturn VI	Mitsubishi Diaqueen ATF-MA1	Tesla Model S, Model 3, and Model X
GM/GMC/Opel/Saturn 88863400	Mitsubishi Diaqueen ATF PA	Toyota THSII/Toyota Prius
GM/GMC/Opel/Saturn 88863401	Nissan Matic Fluid P	
Honda Type 3.0	Nissan Matic Fluid S	