ULTRATUF PLANT GREASE EP2

Code: 8140
Date: 27-04-2018

DESCRIPTION

ULTRATUF PLANT GREASE EP2 is a heavy-duty grease for lubricating anti-friction and plain bearings, operating under high load and/or high temperature conditions found in such industries as steel works, quarries, agriculture, heavy plant machinery, dock side, off shore, etc. Ultratuf Plant Grease EP 2 is fortified using the latest polymer technology and utilises extreme pressure, anti-wear, anti-oxidant, and corrosion inhibiting additives, to give exceptional performance. It provides extended lubrication intervals, especially under arduous conditions and at high operating temperatures. This highly adhesive grease also provides excellent sealing properties against ingress of moisture, dirt, and dust, resulting in extended component life.

SUMMARY OF BENEFITS

- Exceptional mechanical stability for extended lubrication intervals
- Excellent oxidation stability for longer life at high temperatures
- High oil viscosity and anti-wear additives give excellent load bearing performance and wear protection
- Excellent sealing properties to protect against ingress of dirt and dust damage

SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	LITHIUM COMPLEX
TEXTURE	TACKY
COLOUR	DARK RED
DROPPING POINT IP132	250°C MIN
FOUR BALL WELD LOAD IP239	500 KGS
WATER WASHOUT @39°C	3
OPERATING TEMPERATURE RANGE	-20°C to 150°C
BASE OIL CHARACTERISTICS	
BASE OIL	REFINED MINERAL OIL
KV @ 40°C, cST	520

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED