SULFOTEC EP2

Code: 8185
Date: 27-03-2020

DESCRIPTION

SULFOTEC EP2 is a super high-performance grease with exceptional load carrying ability. It is a Calcium Sulfonate which has a natural inherent extreme pressure (EP) properties that stand out from the rest to offer extremely superior wear protection that allows equipment to run at peak performance for longer. Ideal in wet and salty environments even underwater. On top of many automotive, industrial, earthmoving and farm applications, it is also suitable to marine applications, suspension bridges and other applications exposed to salty conditions.

SUMMARY OF BENEFITS

SULFOTEC EP2 is ideal for extreme loads even in wet and salty environments and high temperatures. It's very high load carrying capacity makes it ideal for extreme load conditions and in a wide temperature range. It protects against rust and corrosion and has exceptional water washout resistance. Also ideal for paper mills, steel mills, steamy environments, offshore and underwater applications.

SPECIFICATIONS AND TECHNICAL DATA

NLGI GRADE	2
THICKENER TYPE	CALCIUM SULFONATE
TEXTURE	TACKY
COLOUR	GREEN
DROPPING POINT °C	270 MIN
FOUR BALL WELD LOAD, KGS	800
BASE OIL VISCOSITY @40°C	320 CST
OPERATING TEMPERATURE RANGE °C	-30 to 165+ (for short periods 180C)

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED