

SYNGEAR ULTRASHIFT 40

Code: 9435 Date: 01-07-2020

DESCRIPTION

SYNGEAR ULTRASHIFT 40 is a multipurpose, synthetic, non-EP manual transmission fluid for heavy-duty truck applications. Its advanced formulation provides extended drain and severe service performance. This fluid is suitable for heavy duty manual transmissions such as Mack and Eaton which requires non-EP type fluids.

SUMMARY OF BENEFITS

SYNGEAR ULTRASHIFT 40's low viscosity formulation provides fuel economy. It has excellent oxidation stability and resists sludge formation resulting in longer oil life and extended drain intervals. Its advanced additive system ensures protection from rust, corrosion and wear. Its high viscosity index synthetic base allows the oil to maintain a strong protective film even in high temperature high load conditions. Excellent and smooth shifting performance in all operating conditions.

SPECIFICATIONS

- API Service Category MT-1
- Eaton PS-386, PS=164 Rev 7, Roadranger® extended drain
- International TMS 6816
- Mack Truck TO-A Plus
- Meritor O-81 (Publication TP-90014)
- Spicer Transmission Extended Drain
- Dana synchronized and non-synchronized transmissions

TECHNICAL DATA

CHARACTERISTICS	SYNGEAR ULTRASHIFT 40
Specific gravity at 15 C	0.848
Kinematic viscosity at 40 C, mm2/s (cSt)	96.0
Kinematic viscosity at 100 C, mm2/s (cSt)	15.3
Viscosity index	169

Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com

All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD 151 Colemans Road, Dandenong South VIC 3175 Web: www.tritechlubricants.com Phone: 1300 46 33 33

ASS INTERNATIONAL ISO 9001:2015 RECEICED COMPANY Leuficae No. 4015



AUSTRALIAN MADE AND AUSTRALIAN OWNED