BRAKE FLUID DOT 5.1

Code: 6012
Date: 20-12-2022

DESCRIPTION

BRAKE FLUID DOT 5.1 is a synthetic super high performance polyglycol-based brake fluid designed for use in a wide range of brake and clutch applications where robust and consistent stopping power is desired. BRAKE FLUID DOT 5.1 has a higher boiling point than standard brake fluids and maintains very low viscosities at freezing temperatures. It is recommended for passenger cars, light and heavy commercial vehicles, four-wheel drives and motorcycles where extreme braking is regularly experienced.

SUMMARY OF BENEFITS

DOT 5.1 BRAKE FLUID**,** due to its higher boiling point and good low temperature properties provides peace of mind in all driving conditions, weather and driving styles.
It is compatible with DOT 4 and DOT 3 brake fluids. While mixing with DOT 4 and DOT 3 brake fluids is permissible, one cannot maximize the benefits of using a DOT 5.1 brake fluid.

SPECIFICATIONS

- US FMVSS 116 DOT 5.1, DOT 4, DOT 3
- ISO 4925 (Classes 3, 4, 5.1, 6)
- SAE J1704 / J1703
- AS 1960.1 GRADE 3

TECHNICAL DATA

CHARACTERISTICS	TYPICAL	SPECIFICATION
BOILING POINT °C (MIN DRY ERBP)	273	260
BOILING POINT °C (MIN WET ERBP)	187	180
KINEMATIC VISCOSITY @ -40°C, cSt	721	750 max
DENSITY @20°C, g/ml	1.069	NOT REQUIRED

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED