ATF
SYN HD 668

Code: 9368
Date: 23-06-2023

DESCRIPTION

ATF SYN HD 668 is a full synthetic transmission fluid designed specifically for Allison heavy duty truck and bus transmissions. It is formulated for Allison 1000, 2000, 3000, 4000 Series™, H 40/50 EP™ and eGen Flex™ (Hybrid) on-highway transmissions. It is recommended for applications calling for TES 668 and is also backwards compatible with TES 295, TES 389 and TES 468 applications.
Compared to other transmission fluids, it provides superior anti-wear protection, ani-shudder durability, oxidation resistance resulting in longer fluid life and effective power transfer.

SUMMARY OF BENEFITS

- Improved transmission performance and smoother power transfer
- Extended drain intervals
- Enhanced wear and corrosion protection
- Excellent thermal and oxidation stability
- High viscosity index
- Superior anti-shudder durability

SPECIFICATIONS

- ALLISON TES 668
- ALLISON TES 295
- ALLISON TES 389
- ALLISON TES 468
- DAIMLER DTFR 13C190 (MB 236.92)
- VOLVO 97340 / 97341
- VOITH H55.6335.xx (STANDARD DRAIN & LONG DRAIN)
- MAN 339 TYPE V1
- DANA OHTM ATF-X
- GM D-IIIH
- JASO M315 TYPE 1A
- FORD XT-2-QDX / XT-5-QM

TECHNICAL DATA

CHARACTERISTICS	ATF SYN HD 668
Specific gravity at 15 C	0.8512
Kinematic viscosity at 40 C, mm2/s (cSt)	33.2
Kinematic viscosity at 100 C, mm2/s (cSt)	6.8
Viscosity index	169.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

QAS INTERNATIONAL
ISO 9001:2015
REGISTERED COMPANY
Certificate No. AU1463

AUSTRALIAN MADE AND AUSTRALIAN OWNED