



SYNGEAR LS 75W140 GL5

Code: 9414

Date: 19-04-2022

DESCRIPTION

SYNGEAR LS 75W140 GL5 is a fully synthetic multigrade lubricant providing superior wear protection, high temperature stability and excellent low temperature characteristics due to its blend of selected synthetic base and advance extreme pressure additives. It is formulated to be suitable in limited slip differentials.

SUMMARY OF BENEFITS

SYNGEAR LS 75W140 GL5 is ideal for use in hypoid differentials and limited slip differentials and drive axles. It is designed to give maximum protection to differentials and drive axles operating under the most severe of conditions. It is formulated for outstanding wear protection, seal compatibility, shear stability, and thermal and oxidation stability for extended oil service life. The excellent wear and corrosion protection it provides ensures extended equipment life. It has excellent cold temperature flowability to ensure protection in very cold conditions.

SPECIFICATIONS

- API GL-4/GL-5, LS
- SAE J2360
- MACK GO-J / GO-J PLUS
- SCANIA STO 1:0

TECHNICAL DATA

CHARACTERISTICS	SYNGEAR LS 75W140 GL5
Specific gravity at 15 C	0.8560
Kinematic viscosity at 40 C, mm ² /s (cSt)	171
Kinematic viscosity at 100 C, mm ² /s (cSt)	25.9
Viscosity index	186

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C

TRITECH LUBRICANTS AND SALES PTY LTD
151 Colemans Road, Dandenong South VIC 3175
Web: www.tritechlubricants.com
Phone: 1300 46 33 33

